

Description

tube outer diameter: 3/16", thread: 3/8-24, 37°, flared union - male to male corrosion resistant steel"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN8153J
Minimum Qty (MOQ):	2
NSN:	4730-00-540-0487
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N AN815-3J Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	225.0 Deg Fahrenheit 1st Response
End Item Identification:	11f Aircraft, Galaxy C-5
Connection Style:	Flared W/ Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.375 Inches All Ends
Nominal Overall Length:	1.218 Inches
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid 1st Response
Media For Which Designed:	Oxygen, Gaseous 2nd Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Inside
Style Designator:	Flared W/ Center Wrenching Facility
Thread Series Designator:	Unjf All Ends
Furnished Items And Quantity:	2 Preformed Packing
Specification/standard Data:	88044-an815 Government Standard

How to Order

Order this boss nipple from our inventory online by visiting <https://military-fasteners.com/fittings/boss+nipples/AN815-3J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.