

Description

outer diameter: 1/8" pipe diameter: 1/8", thread: 5/16-24, straight pipe to 37 degree, flared tube, corrosion resistant steel, AN816 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN8162J |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-720-0182 |
| ECCN: | 9A991 |
| National Motor Freight: | 052250, Pipe R Tubing R Pipe Fittings Noi |



* See page 2 for technical characteristics

P/N AN816-2J Specifications

| | |
|---|---|
| Thread Class: | 3a 2nd End |
| Connection Style: | Flared W/ Gasket Seal (boss) 2nd End |
| Connection Style: | Plain (pipe) 1st End |
| Connection Type: | Threaded External Boss 2nd End |
| Connection Type: | Threaded External Pipe 1st End |
| Nominal Thread Size: | 0.125 Inches 1st End |
| Nominal Thread Size: | 0.312 Inches 2nd End |
| Nominal Overall Length: | 1.016 Inches |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Inside |
| Surface Treatment: | Passivate Outside |
| Surface Treatment Document And Classification: | Mil-f-14072,e300,ty2 Mil Spec Single Treatment Response Outside |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Inside |
| Thread Series Designator: | Anpt 1st End |
| Thread Series Designator: | Unjf 2nd End |
| Specification/standard Data: | 81343-as4842/1 Professional/Industrial Association Standard |

How to Order

Order this straight pipe to boss adapter from our inventory online by visiting <https://military-fasteners.com/fittings/straight+pipe+to+boss+adapters/AN816-2J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.