

# P/N AN816-4-4J

Military-Fasteners.com

### Description

tube outer diameter: 1/4" pipe diameter: 1/4", thread: 7/16-20, straight pipe to flared tube, corrosion resistant steel, AN816 series fitting

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

AS5194J0404	
SKU / Model:	AN81644J
Minimum Qty (MOQ):	2
NSN:	4730-00-911-7127
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



### P/N AN816-4-4J Specifications

Thread Class:	3a 2nd End
Connection Style:	Flared W/ Gasket Seal (boss) 2nd End
Connection Style:	Plain (pipe) 1st End
Connection Type:	Threaded External Boss 2nd End
Connection Type:	Threaded External Pipe 1st End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.250 Inches 1st End
Nominal Thread Size:	0.438 Inches 2nd End
Nominal Overall Length:	1.375 Inches
Special Features:	Center Wrenching Facility
Material:	Steel Comp 304 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Anpt 1st End
Thread Series Designator:	Unjf 2nd End
Furnished Items And Quantity:	1 Preformed Packing
Specification/standard Data:	88044-an816 Government Standard And 81343-as4842/1 Professional/industrial Association Standard

### How to Order

Order this straight pipe to boss adapter from our inventory online by visiting <u>https://military-fasteners.com/fittings/straight+pipe+to+boss+adapters/AN816-4-4J</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.