

Description

tube outer diameter: 5/16" pipe diameter: 1/4", thread: 1/2-20, straight pipe to 37°, flared tube - corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN81654J
Minimum Qty (MOQ):	1
NSN:	4730-00-842-6484
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

P/N AN816-5-4J Specifications

Thread Class:	3a 2nd End
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
Connection Style:	Flared W/ Gasket Seal (boss) 2nd End
Connection Style:	Plain (pipe) 1st End
Connection Type:	Threaded External Boss 2nd End
Connection Type:	Threaded External Pipe 1st End
Nominal Thread Size:	0.250 Inches 1st End
Nominal Thread Size:	0.500 Inches 2nd End
Nominal Overall Length:	1.375 Inches
Special Features:	Center Wrenching Facility
Material:	Steel Comp 304 Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Passivate Overall
Thread Series Designator:	Anpt 1st End
Thread Series Designator:	Unjf 2nd End
Specification/standard Data:	88044-an816 Government Standard And 81343-as4842/1 Professional/industrial Association Standard

How to Order

Order this straight pipe to boss adapter from our inventory online by visiting <https://military-fasteners.com/fittings/straight+pipe+to+boss+adapters/AN816-5-4J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.