

P/N AN824-6J

Description

tube outer diameter: 3/8", thread: 9/16-18, flared tube, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN8246J

Minimum Qty (MOQ):

NSN: 4730-00-278-9463

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N AN824-6J Specifications

Thread Class:	3a All Ends
Maximum Operating Temp:	-65.0 Deg Fahrenheit 2nd Response
Maximum Operating Temp:	225.0 Deg Fahrenheit 1st Response
Connection Style:	Flared (tube) All Ends
Leg Length:	1.0312 Inches Nominal All Ends
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.562 Inches All Ends
Seat Angle:	37.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.375 Inches All Ends
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Media For Which Designed:	Fluid 1st Response
Media For Which Designed:	Oxygen, Gaseous 2nd Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,ty 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends

How to Order

Order this tube tee from our inventory online by visiting https://military-fasteners.com/fittings/tube+tees/AN824-6] and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.