

P/N AN827-8

Description

tube outer diameter: 1/2", thread: 3/4-16, flared tube - steel"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN8278	
Minimum Qty (MOQ):	1	
NSN:	4730-00-277-7953	

National Motor Freight: 052190, Pipe, tubing, or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N AN827-8 Specifications

Thread Class:	2a All Ends
Maximum Operating Temp:	400.0 Deg Fahrenheit Single Response
End Item Identification:	Aircraft Application
Connection Style:	Flared (tube) All Ends
Leg Length:	1.250 Inches Nominal All Ends
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.750 Inches All Ends
Seat Angle:	37.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.500 Inches All Ends
Material:	Steel Overall
Surface Treatment Document And Classification:	J514 Assn Std Single Treatment Response Overall And Qq-p-416, Ty 1, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf All Ends
Furnished Items And Quantity:	4 Short Coupling Nut And 4 Ferrule Sleeve
Specification/standard Data:	88044-an827 Government Standard And 81343-as4841 Professional/industrial Association Standard
Nondefinitive Spec/std Data:	6c Figure

How to Order

Order this tube cross from our inventory online by visiting https://military-fasteners.com/fittings/tube+crosses/AN827-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/tube+crosses/AN827-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/tube+crosses/AN827-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/fittings/tube+crosses/AN827-8 and selecting the quantity you want then