

P/N AN832-10J

Description

tube outer diameter: 5/8", thread: 7/8-14, flared tube - 3/8" bulkhead and universal, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN83210J

Minimum Qty (MOQ):

NSN: 4730-00-720-1256

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N AN832-10J Specifications

| Thread Class: | 3a 1st End Bulkhead |
|--|---|
| Thread Class: | 3a All Ends |
| Connection Style: | Flared (tube) 1st End |
| Connection Style: | Flared W/ Gasket Seal (boss) 2nd End |
| Connection Type: | Threaded External Boss 2nd End |
| Connection Type: | Threaded External Tube 1st End |
| Nominal Thread Size: | 0.875 Inches 1st End Bulkhead |
| Nominal Thread Size: | 0.875 Inches All Ends |
| Seat Angle: | 37.0 Degrees 1st End |
| Nominal Outside Diameter Tube Accommodated: | 0.625 Inches 1st End |
| Nominal Overall Length: | 2.719 Inches |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Inside |
| Thread Series Designator: | Unjf All Ends |
| Thread Series Designator: | Unjf 1st End Bulkhead |
| Specification/standard Data: | 88044-an832 Government Standard And 81343-as4841 Professional/industrial Association Standard |

How to Order

Order this straight tube to boss adapter from our inventory online by visiting https://military-fasteners.com/fittings/straight+tube+to+boss+adapters/AN832-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.