

P/N AN832-2J

Description

tube outer diameter: 1/8", thread: 5/16-24, flared tube, 3/8 bulkhead and universal, corrosion resistant steel, AN832 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN8322J

Minimum Qty (MOQ):

NSN: 4730-00-622-1616

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



^{*} See page 2 for technical characteristics

P/N AN832-2J Specifications

Thread Class:	3a 1st End Bulkhead
Thread Class:	3a All Ends
Connection Style:	Flared (tube) 1st End
Connection Style:	Flared W/ Gasket Seal (boss) 2nd End
Connection Type:	Threaded External Boss 2nd End
Connection Type:	Threaded External Tube 1st End
Nominal Thread Size:	0.312 Inches 1st End Bulkhead
Nominal Thread Size:	0.312 Inches All Ends
Seat Angle:	37.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.125 Inches 1st End
Nominal Overall Length:	1.828 Inches
Material:	Steel Comp 304 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Inside
Thread Series Designator:	Unjf All Ends
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	88044-an832 Government Standard And 81343-as4841 Professional/industrial Association Standard

How to Order

Order this straight tube to boss adapter from our inventory online by visiting https://military-fasteners.com/fittings/straight+tube+to+boss+adapters/AN832-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.