

**Description**

tube outer diameter: 3/8", thread: 9/16-18, flared tube, 3/8 bulkhead and universal, corrosion resistant steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AS5406J06](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN8326J                                     |
| Minimum Qty (MOQ):      | 2   |
| NSN:                    | 4730-00-510-7192                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



\* See page 2 for technical characteristics

## P/N AN832-6J Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a 1st End Bulkhead   |
| <b>Thread Class:</b>                                  | 3a All Ends   |
| <b>End Item Identification:</b>                       | 23n Ship, Ohio Class Ssn (trident)  |
| <b>Connection Style:</b>                              | Flared (tube) 1st End   |
| <b>Connection Style:</b>                              | Flared W/ Gasket Seal (boss) 2nd End  |
| <b>Connection Type:</b>                               | Threaded External Boss 2nd End  |
| <b>Connection Type:</b>                               | Threaded External Tube 1st End  |
| <b>Nominal Thread Size:</b>                           | 0.562 Inches 1st End Bulkhead   |
| <b>Nominal Thread Size:</b>                           | 0.562 Inches All Ends   |
| <b>Seat Angle:</b>                                    | 37.0 Degrees 1st End  |
| <b>Nominal Outside Diameter Tube Accommodated:</b>    | 0.375 Inches 1st End  |
| <b>Nominal Overall Length:</b>                        | 2.219 Inches  |
| <b>Material:</b>                                      | Steel Comp 304 Overall  |
| <b>Material Document And Classification:</b>          | 66 Fed Std Single Material Response Overall   |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-f-14072,e300,ty 2 Mil Spec Single Treatment Response Outside                              |
| <b>Surface Treatment Document And Classification:</b> | Mil-s-5002 Mil Spec Single Treatment Response Inside  |
| <b>Thread Series Designator:</b>                      | Unjf All Ends   |
| <b>Thread Series Designator:</b>                      | Unjf 1st End Bulkhead   |
| <b>Specification/standard Data:</b>                   | 88044-as832 Government Standard And 81343-as4841 Professional/Industrial Association Standard |

## How to Order

Order this straight tube to boss adapter from our inventory online by visiting <https://military-fasteners.com/fittings/straight+tube+to+boss+adapters/AN832-6J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.