

Description

outer diameter: 3/4", thread: 1-1/16-12, 90 degree, flared tube, bulkhead universal, corrosion resistant steel, AN833 series elbow

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS1038J1212](#)

| | |
|-------------------------|---|
| SKU / Model: | AN83312J |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-618-7556 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N AN833-12J Specifications

| | |
|---|---|
| Thread Class: | 3a 1st End Bulkhead |
| Thread Class: | 3a All Ends |
| Connection Style: | Flared (tube) All Ends |
| Leg Length: | 1.756 Inches Nominal 2nd End |
| Leg Length: | 2.656 Inches Nominal 1st End |
| Connection Type: | Threaded External Tube All Ends |
| Thread Quantity Per Inch: | 12 1st End Bulkhead |
| Thread Quantity Per Inch: | 12 All Ends |
| Nominal Thread Size: | 1.062 Inches 1st End Bulkhead |
| Nominal Thread Size: | 1.062 Inches All Ends |
| Seat Angle: | 37.0 Degrees All Ends |
| Flow Angle: | 90.0 Degrees |
| Nominal Outside Diameter Tube Accommodated: | 0.750 Inches All Ends |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-f-14072,e300,ty2 Mil Spec Single Treatment Response Outside |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Inside |
| Thread Series Designator: | Unj 1st End Bulkhead |
| Thread Series Designator: | Unj All Ends |
| Specification/standard Data: | 88044-an833 Government Standard |

How to Order

Order this tube elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+elbows/AN833-12J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.