

Description

hose inner diameter: 3/8", tube outer diameter: 3/8", thread: 9/16-18, flared tube to hose - aluminum

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN8386D
Minimum Qty (MOQ):	1
NSN:	4730-00-194-1059
National Motor Freight:	051400, Pipe Fittings Aluminum

NO IMAGE
AVAILABLE

P/N AN838-6D Specifications

Thread Class:	3a 1st End
Thread Class:	3a 1st End Bulkhead
Connection Style:	Beaded (hose) 2nd End
Connection Style:	Flared (tube) 1st End
Leg Length:	1.734 Inches Nominal 1st End
Leg Length:	1.937 Inches Nominal 2nd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Unthreaded External Hose 2nd End
Nominal Thread Size:	0.562 Inches 1st End
Nominal Thread Size:	0.562 Inches 1st End Bulkhead
Seat Angle:	37.0 Degrees 1st End
Flow Angle:	90.0 Degrees
Nominal Inside Diameter Hose Accommodated:	0.375 Inches 2nd End
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/6,t6 Fed Spec 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid 1st Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf 1st End
Thread Series Designator:	Unjf 1st End Bulkhead
Specification/standard Data:	88044-an838 Government Standard

How to Order

Order this tube to hose elbow from our inventory online by visiting <https://military-fasteners.com/fittings/tube+to+hose+elbows/AN838-6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.