

P/N AN894D8-4

Military-Fasteners.com

### Description

female straight to male, screw thread expander, aluminum

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS24398D8-4	
SKU / Model:	AN894D84
Minimum Qty (MOQ):	1
NSN:	4730-00-684-7292
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



# P/N AN894D8-4 Specifications

Thread Class:	3a 2nd End
Thread Class:	3b 1st End
Maximum Operating Temp:	250.0 Deg Fahrenheit Single Response
Connection Style:	Flared (tube) 1st End
Connection Style:	Gasket Seal (boss) 2nd End
Connection Type:	Threaded External Tube 1st End
Connection Type:	Threaded Internal Boss 2nd End
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches 2nd End
Nominal Thread Size:	0.750 Inches 1st End
Seat Angle:	37.0 Degrees 1st End
Nominal Outside Diameter Tube Accommodated:	0.250 Inches 1st End
Nominal Overall Length:	1.609 Inches
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec Single Material Response Overall Or Qq-a-225/6,t6 Or T851 Fed Spec Single Material Response Overall
Media For Which Designed:	Fluid 1st Response
Media For Which Designed:	Oxygen, Gaseous 2nd Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type2,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf 2nd End
Thread Series Designator:	Unjf 1st End
Specification/standard Data:	81343-as4875/1 Professional/industrial Association Standard

# **How to Order**

Order this straight tube to boss adapter from our inventory online by visiting <u>https://military-fasteners.com/fittings/straight+tube+to+boss+adapters/AN894D8-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.