

P/N AN9-30

Description

Fastener Length: 3-1/8", Thread: 1/2-18, Thread Length: 7/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN930
Minimum Qty (MOQ):	1
NSN:	5306-00-151-3129
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN9-30 Specifications

Thread Class: 3a	
Thread Direction: Right	ght-hand
Thread Length: 0.90	906 Inches Minimum
Fastener Length: 3.15	156 Inches Nominal
Head Style: Hex	exagon
Head Height: 0.29	296 Inches Minimum And 0.328 Inches Maximum
Width Between Flats: 0.86	865 Inches Minimum And 0.877 Inches Maximum
Shank Unthreaded Hole Diameter: 0.14	141 Inches Nominal First Hole
Nominal Thread Diameter: 0.56	562 Inches
Grip Length: 2.25	250 Inches Nominal
Features Provided: Finis	nished Head
Thread Quantity Per Inch: 18	
Minimum Tensile Strength: 125	5000 Pounds Per Square Inch
Hardness Rating: 26.0	.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	906 Inches Nominal First Hole
Material:	eel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel omp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification: Mil-	l-b-6812 Mil Spec All Material Responses Overall
Surface Treatment: Cad	dmium Overall And Chromate Overall
Surface Treatment Document And Classification: Qq-	q-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN9-30 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.