

P/N AN9-34

Military-Fasteners.com

### Description

AN9-34 Machine Bolt

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AN934
Minimum Qty (MOQ):	5
NSN:	5306-00-151-3018
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## **P/N AN9-34 Specifications**

Interact Uass:34Thread Uass:35Thread Direction:Right-handThread Length:0.906 Inches MinimumFastener Length:3.656 Inches NominalHead Style:HexagonHead Height:0.296 Inches Minimum And 0.328 Inches MaximumWidth Between Flats:0.6865 Inches Minimum And 0.327 Inches MaximumShank Unthreaded Hole Diameter:0.141 Inches Nominal First HoleNominal Thread Diameter:0.562 InchesStank Unthreaded Hole Diameter:0.562 InchesOrip Length:2.750 Inches NominalFratures Provided:Finished HeadThread Ouanity Per Inch:18Barnes Strating:0.500 Pounds Per Square InchHardenes Rating:0.500 Pounds Per Square InchDistance From Head Largest3.406 Inches Nominal First HoleCenter:3.406 Inches Nominal First HoleCenter:3.406 Inches Nominal First HoleMaterial Document And Classification:Mile-Soday Mill Spec 1st Material Response Overall Or Mile-Sodo Mill Spec 2nd Material Response Overall Or Mile-Soda Spic Mill Spec 3th Material Response OverallSurface Treatment:Camium Overall And Chromate OverallSurface Treatment:Camium Overall And Chromate OverallSurface Treatment Document And Classification:Guile Spic St Material Response OverallSurface Treatment:Camium Overall And Chromate OverallS	Thread Class:	За
Thread Length:0.906 Inches MinimumFastener Length:3.656 Inches NominalHead Style:HexagonHead Height:0.296 Inches Minimum And 0.328 Inches MaximumWidth Between Flats:0.865 Inches Minimum And 0.877 Inches MaximumShark Unthreaded Hole Diamete:0.414 Inches Nominal First HoleNominal Thread Diameter:0.562 Inches Minimum And 0.877 Inches MaximumThread Quantity Per Inche:0.562 Inches NominalFratures Provided:1.500 Inches NominalThread Quantity Per Inche:1.5000 Pounds Per Square InchBardingsurger Strating:0.600 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallBardingsurger Strating:0.400 Inches Nominal First HoleMarcing Surface:Acon Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallBarding Surface:Scolon Pounds Per Square InchMaterial:0.600 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallMarcing Surface:Acon Rockwell C Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial:Scolon Strato Porse Overall Or Steel Comp 8630 Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec Stef		
Fastener Length:3.656 Inches NominalHead Style:HexagonHead Height:0.296 Inches Minimum And 0.328 Inches MaximumWidth Between Flats:0.865 Inches Minimum And 0.877 Inches MaximumShank Unthreaded Hole Diamete:0.141 Inches Nominal First HoleNominal Thread Diameter:0.552 InchesGrip Length:0.552 Inches NominalFeatures Provided:Finished HeadThread Quantity Per Inch:18Minimum Tensile Strength:12500 Pounds Per Square InchBistance From Head Larges2.060 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallPaterial Surface To Shark Hole Center:Stel Comp 8740 Overall On Stel Comp 8630 Overall On Stel Comp 8735 Overall On Stel Comp 4130 OverallMaterial Document And Classification:Mil-s6049 Mil Spec 1st Material Response Overall On Mil-s-6050 Mil Spec 2nd Material Response Overall On Mil-s-6050 Mil Spec 2nd Material Response Overall On Stel Comp 4130 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment And Classification:Cadmium Overall And Chromate Overall <t< th=""><th>Thread Direction:</th><th>Right-hand</th></t<>	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.296 Inches Minimum And 0.328 Inches MaximumWidth Between Flats:0.865 Inches Minimum And 0.877 Inches MaximumShank Unthreaded Hole Diametr:0.141 Inches Nominal First HoleNominal Thread Diametr:0.562 Inches0.562 Inches0.562 InchesFreatures Provided:1.570 Inches NominalFreatures Provided:1.8Minimum Tensile Strength:1.25000 Pounds Per Square InchBistance From Head Largest Bearing Surface To Shank Hole2.600 nounds Per Square InchNaterial:0.400 Inches Nominal First HoleMaterial:0.600 nounds Per Square InchMaterial:0.600 nounds Per Square InchMaterial:0.600 nounds Per Square InchMaterial:0.400 Inches Nominal First HoleDistance From Head Largest Bearing Surface To Shank Hole3.400 Inches Nominal First HoleMaterial:0.600 nourceall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial:0.611.5600 Akini Jispec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Amile-St St St Mil Spec 5t Miterial Response Overall Or Ams 6300 Akin Sh St dt Histerial Response Overall Or Amile-St St Mil Spec 6t Histerial Response Overall Or Amile-St St St Mil Spec 6t Histerial Response Overall Or Amile-St St Mil Spec 6t Histerial Response Overall Or	Thread Length:	0.906 Inches Minimum
Head Height:0.296 Inches Minimu And 0.328 Inches MaximumWidth Between Flats:0.865 Inches Minimu And 0.877 Inches MaximumShank Unthreaded Hole Diameter:0.141 Inches Nominal First HoleNominal Thread Diameter:0.562 InchesOpfiength:0.552 Inches NominalFratures Provided:1500 Pounds Per Square InchHead Quantity Per Inch:125000 Pounds Per Square InchHardness Rating:26.00 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3406 Inches Nominal First HoleMaterial Document And Cissification:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallSurface Treatment:Cadmium Overall And Scion Ass St dt Hin Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec	Fastener Length:	3.656 Inches Nominal
Width Beween Flats:0.865 Inches Minimum And 0.877 Inches MaximumShank Unthreaded Hole Diameter:0.141 Inches Nominal First HoleNominal Thread Diameter:0.562 InchesGrip Length:2.750 Inches NominalFeatures Provided:Finished HeadThread Quantity Per Inch:18Minimum Tensile Strength:25000 Pounds Per Square InchBarding:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial Document And Classification:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallSurface Treatment:Cadmium Overall And Ersponse Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec Sth Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3nd Material Response O	Head Style:	Hexagon
Shank Unthreaded Hole Diameter:0.141 Inches Nominal First HoleNominal Thread Diameter:0.562 InchesGrip Length:2.750 Inches NominalFeatures Provided:Finished HeadThread Quantity Per Inch:18Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3 Fed Sponse OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Oq-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Head Height:	0.296 Inches Minimum And 0.328 Inches Maximum
Nominal Thread Diameter:0.562 InchesGrip Length:2.750 Inches NominalFeatures Provided:Finished HeadThread Quantity Per Inch:18Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Sili-s-6039 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,class 3 Fed Spec All Treatment Response Overall	Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Length:2.750 Inches NominalFeatures Provided:Finished HeadThread Quantity Per Inch:18Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Steel Comp 6740 Overall Or Steel Comp 8630 Assn Std 4th Material Response Overall Or Mil-s-6058 Mil Spec 3rd Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qrp-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Shank Unthreaded Hole Diameter:	0.141 Inches Nominal First Hole
Features Provided:Finished HeadThread Quantity Per Inch:18Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.562 Inches
Thread Quantity Per Inch:18Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Grip Length:	2.750 Inches Nominal
Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn 5td 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Overall Or Ams 6300 Assn 5td 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Overall Or Ams 6300 Assn 5td 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Mil-s-6758 Mil Spec 6th Material Response Overall OverallSurface Treatment:Cadmium Overall And Chromate Overall Oq-p-416,ty 2,class 3 Fed Spec All Treatment Response Overall	Features Provided:	Finished Head
Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallOq-p-416,ty 2,class 3 Fed Spec All Treatment Responses OverallOverall	Thread Quantity Per Inch:	18
Distance From Head Largest Bearing Surface To Shank Hole Center:3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center:3.406 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall Qu-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Bearing Surface To Shank Hole	3.406 Inches Nominal First Hole
Material Document And Classification:Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,class 3 Fed Spec All Treatment Response Overall	Material:	
Surface Treatment Document And Classification:		Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or
Classification: Qq-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf		Qq-p-416,ty 2,class 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

# How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/AN9-34</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.