

# P/N AN919-1

### **Description**

outer diameter: 1/4", thread: 7/16-20, steel, male to male external thread, flared tube, large end

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN9191

Minimum Qty (MOQ):

NSN: 4730-00-804-1906

ECCN: 9A991

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti









<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN919-1 Specifications**

Thread Class:	3a All Ends
Reducer Type:	Concentric
Connection Style:	Flared W/ Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.312 Inches 2nd End
Nominal Thread Size:	0.438 Inches 1st End
Nominal Overall Length:	1.250 Inches
Material:	Steel Overall
Material Document And Classification:	Qq-s-637 Fed Spec Single Material Response Overall Or Mil-s-6758 Mil Spec Single Material Response Overall And Mil-s-5626 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Furnished Items And Quantity:	2 Preformed Packing
Specification/standard Data:	96906-ms24399 Government Standard And 81349-mil-5509 Government Specification

# **How to Order**

Order this boss reducer from our inventory online by visiting <a href="https://military-fasteners.com/fittings/boss+reducers/AN919-1">https://military-fasteners.com/fittings/boss+reducers/AN919-1</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.