

Description

steel, male to male external thread, flared tube, large end, tube outer diameter: 1/2", thread: 3/4-16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN91910 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-235-1501 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |

NO IMAGE
AVAILABLE

P/N AN919-10 Specifications

| | |
|--|--|
| Thread Class: | 3a All Ends |
| Reducer Type: | Concentric |
| Maximum Operating Temp: | 275.0 Deg Fahrenheit Single Response |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Maximum Operating Pressure: | 3000.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 0.438 Inches 2nd End |
| Nominal Thread Size: | 0.750 Inches 1st End |
| Criticality Code Justification: | Feat |
| Nominal Overall Length: | 1.531 Inches |
| Special Features: | Weapon System Essential |
| Material: | Steel Comp 1137 Overall Or Steel Comp 1141 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf All Ends |
| Furnished Items And Quantity: | 2 Preformed Packing |

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.