

## **P/N AN919-10**

### **Description**

steel, male to male external thread, flared tube, large end, tube outer diameter: 1/2", thread: 3/4-16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN91910
Minimum Qty (MOQ):	2

NSN: 4730-00-235-1501

ECCN: EAR99

National Motor Freight: 052190, Pipe,tubing,or Pipe Or Tubing Fitti



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN919-10 Specifications

Thread Class:	3a All Ends
Reducer Type:	Concentric
Maximum Operating Temp:	275.0 Deg Fahrenheit Single Response
Connection Style:	Flared W/ Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.438 Inches 2nd End
Nominal Thread Size:	0.750 Inches 1st End
Criticality Code Justification:	Feat
Nominal Overall Length:	1.531 Inches
Special Features:	Weapon System Essential
Material:	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf All Ends
Furnished Items And Quantity:	2 Preformed Packing

## **How to Order**

Order this boss reducer from our inventory online by visiting <a href="https://military-fasteners.com/fittings/boss+reducers/AN919-10">https://military-fasteners.com/fittings/boss+reducers/AN919-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.