

**Description**

tube outer diameter: 5/8", thread: 7/8-14, steel, male to male external thread, flared tube, large end, AN919 series reducer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN91915
Minimum Qty (MOQ):	1
NSN:	4730-00-235-1506
Schedule B:	7318.15.4000
ECCN:	9A991
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



## P/N AN919-15 Specifications

<b>Thread Class:</b>	3a All Ends
<b>Maximum Operating Temp:</b>	275.0 Deg Fahrenheit Single Response
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) All Ends
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.750 Inches 2nd End
<b>Nominal Thread Size:</b>	0.875 Inches 1st End
<b>Nominal Overall Length:</b>	1.750 Inches
<b>Material:</b>	Steel Comp 1137 Overall Or Steel Comp 1141 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf 2nd End
<b>Thread Series Designator:</b>	Unjf 1st End
<b>Specification/standard Data:</b>	88044-an919 Government Standard

## How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.