

**Description**

tube outer diameter: 5/8", thread: 7/8-14, aluminum, male to male external thread, flared tube, large end, AN919 series fitting

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AS5174D1008](#)

SKU / Model:	AN91915D
Minimum Qty (MOQ):	1
NSN:	4730-00-187-3588
Schedule B:	7609.00.0000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



\* See page 2 for technical characteristics

## P/N AN919-15D Specifications

<b>Thread Class:</b>	3a All Ends
<b>Reducer Type:</b>	Concentric
<b>Maximum Operating Temp:</b>	275.0 Deg Fahrenheit Single Response
<b>End Item Identification:</b>	Aircraft Fluid Systems
<b>Connection Style:</b>	Flared W/ Gasket Seal (boss) All Ends
<b>Connection Type:</b>	Threaded External Boss All Ends
<b>Maximum Operating Pressure:</b>	3000.0 Pounds Per Square Inch Single Response
<b>Nominal Thread Size:</b>	0.750 Inches 2nd End
<b>Nominal Thread Size:</b>	0.875 Inches 1st End
<b>Nominal Overall Length:</b>	1.750 Inches
<b>Material:</b>	Aluminum Alloy 2014 Overall
<b>Material Document And Classification:</b>	Qq-a-225/4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Thread Series Designator:</b>	Unf 2nd End
<b>Thread Series Designator:</b>	Unjf 1st End
<b>Specification/standard Data:</b>	88044-an919 Government Standard

## How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.