

Description

aluminum - male to male external thread - 37°, flared tube - large end - tube outer dia: 3/4", thread: 1-1/16-12

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN91917D
Minimum Qty (MOQ):	1
NSN:	4730-00-187-3590
National Motor Freight:	051400, Pipe Fittings Aluminum



P/N AN919-17D Specifications

Thread Class:	3a All Ends
Reducer Type:	Concentric
Maximum Operating Temp:	160.0 Deg Fahrenheit Single Response
End Item Identification:	Aircraft Application
Connection Style:	Flared W/ Gasket Seal (boss) All Ends
Connection Type:	Threaded External Boss All Ends
Thread Quantity Per Inch:	12 1st End
Maximum Operating Pressure:	1500.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.500 Inches 2nd End
Nominal Thread Size:	1.062 Inches 1st End
Nominal Overall Length:	1.797 Inches
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material:	Aluminum Alloy 2014 Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec Single Material Response Overall Or Qq-a-225/6,t6 Fed Spec Single Material Response Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec Single Material Response Or Qq-a-225/6,t6 Fed Spec Single Material Response Overall
Media For Which Designed:	Hydraulic Fluid 1st Response
Media For Which Designed:	Oxygen, Gaseous 2nd Response
Surface Treatment:	Anodize Overall
Thread Series Designator:	Un 1st End
Thread Series Designator:	Unf 2nd End
Specification/standard Data:	96906-ms24399 Government Standard
Specification/standard Data:	81343-as5174 Government Specification

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-17D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.