

Description

tube outer diameter: 3/4", thread: 1-1/16-12, male to male external thread, flared tube, large end, steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN91919 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-235-1510 |
| ECCN: | 9A991 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |

NO IMAGE
AVAILABLE

P/N AN919-19 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a All Ends |
| Reducer Type: | Concentric |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Thread Quantity Per Inch: | 12 1st End |
| Nominal Thread Size: | 0.750 Inches 2nd End |
| Nominal Thread Size: | 1.062 Inches 1st End |
| Nominal Overall Length: | 1.891 Inches |
| Material: | Steel Comp 1137 Overall Or Steel Comp 1141 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Un 1st End |
| Thread Series Designator: | Unf 2nd End |
| Specification/standard Data: | 88044-an919 Government Standard |

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.