

Description

aluminum male to male external thread flared tube large end tube outer dia: 3/4", thread: 1-1/16-12

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS5174D1210](#)

SKU / Model:	AN91920D
Minimum Qty (MOQ):	2
NSN:	4730-00-805-5100
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



P/N AN919-20D Specifications

Thread Class:	3a All Ends
Reducer Type:	Concentric
Maximum Operating Temp:	225.0 Deg Fahrenheit Single Response
Connection Style:	Flared (tube) All Ends
Connection Type:	Threaded External Tube All Ends
Thread Quantity Per Inch:	12 1st End
Nominal Thread Size:	0.875 Inches 2nd End
Nominal Thread Size:	1.062 Inches 1st End
Seat Angle:	37.0 Degrees All Ends
Criticality Code Justification:	Feat
Nominal Outside Diameter Tube Accommodated:	0.625 Inches 2nd End
Nominal Outside Diameter Tube Accommodated:	0.750 Inches 1st End
Nominal Overall Length:	2.000 Inches
Special Features:	Supports Grumman A10a Aircraft;weapon System Essential
Material:	Aluminum Alloy 2014 Overall Or Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-225/4,t6 Fed Spec 1st Material Response Overall Or Qq-a-225/6,t6 Fed Spec 2nd Material Response Overall
Media For Which Designed:	Hydraulic Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2,cl 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unj 1st End
Thread Series Designator:	Unjf 2nd End
Specification/standard Data:	96906-ms24399 Government Standard And 81349-mil-f-5509 Government Specification

How to Order

Order this tube reducer from our inventory online by visiting <https://military-fasteners.com/fittings/tube+reducers/AN919-20D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.