

Description

AN919-21 Boss Reducer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN91921 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-235-1512 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN919-21 Specifications

| | |
|---|---|
| Thread Class: | 3a All Ends |
| Reducer Type: | Concentric |
| Maximum Operating Temp: | 160.0 Deg Fahrenheit Single Response |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Thread Quantity Per Inch: | 12 1st End |
| Maximum Operating Pressure: | 1500.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 1.312 Inches 1st End |
| Nominal Thread Size: | 0.438 Inches 2nd End |
| Nominal Overall Length: | 1.844 Inches |
| Material: | Steel Comp 1137 Overall Or Steel Comp 1141 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Media For Which Designed: | Hydraulic Fluid Single Response |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Un 1st End |
| Thread Series Designator: | Unf 2nd End |
| Specification/standard Data: | 88044-an919 Government Standard |

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.