

Description

aluminum, male to male external thread, flared tube, large end, tube outer dia: 1", thread: 1-5/16-12

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------|
| SKU / Model: | AN91923D |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-187-3596 |
| ECCN: | EAR99 |
| National Motor Freight: | 051400, Pipe Fittings Aluminum |

NO IMAGE
AVAILABLE

P/N AN919-23D Specifications

| | |
|--|--|
| Thread Class: | 3a All Ends |
| Reducer Type: | Concentric |
| Maximum Operating Temp: | 160.0 Deg Fahrenheit Single Response |
| End Item Identification: | Aircraft Aplication |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Thread Quantity Per Inch: | 12 All Ends |
| Maximum Operating Pressure: | 1500.0 Pounds Per Square Inch Single Response |
| Nominal Thread Size: | 1.312 Inches 1st End |
| Nominal Thread Size: | 1.062 Inches 2nd End |
| Nominal Overall Length: | 2.156 Inches |
| Material: | Aluminum Alloy 2014 Overall |
| Material Document And Classification: | Qq-a-225/4,t6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Thread Series Designator: | Un All Ends |
| Specification/standard Data: | 81343-as5174 Professional/industrial Association Specification |

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-23D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.