

Description

outer diameter: 3/8", thread: 9/16-18, steel, male to male external thread, 37 degree, flared, AN919 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AS5174-0604](#)

| | |
|-------------------------|---|
| SKU / Model: | AN9196 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-187-3600 |
| Schedule B: | 7326.90.8688 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



* See page 2 for technical characteristics

P/N AN919-6 Specifications

| | |
|--|---|
| Thread Class: | 3a All Ends |
| Reducer Type: | Concentric |
| Connection Style: | Flared W/ Gasket Seal (boss) All Ends |
| Connection Type: | Threaded External Boss All Ends |
| Nominal Thread Size: | 0.438 Inches 2nd End |
| Nominal Thread Size: | 0.562 Inches 1st End |
| Nominal Overall Length: | 1.406 Inches |
| Material: | Steel Comp 1137 Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf 2nd End |
| Thread Series Designator: | Unjf 1st End |
| Specification/standard Data: | 88044-an919 Government Standard |

How to Order

Order this boss reducer from our inventory online by visiting <https://military-fasteners.com/fittings/boss+reducers/AN919-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.