

Description

AN919-6J Tube Reducer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN9196J
Minimum Qty (MOQ):	1
NSN:	4730-00-023-4888
Schedule B:	7307.29.0000
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN919-6J Specifications

Thread Class:	3a All Ends
Reducer Type:	Concentric
Connection Style:	Flared (tube) All Ends
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.375 Inches 2nd End
Nominal Thread Size:	0.562 Inches 1st End
Seat Angle:	37.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.188 Inches 2nd End
Nominal Outside Diameter Tube Accommodated:	0.375 Inches 1st End
Nominal Overall Length:	1.328 Inches
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms24399 Government Standard

How to Order

Order this tube reducer from our inventory online by visiting <https://military-fasteners.com/fittings/tube+reducers/AN919-6J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.