

P/N AN924-16S

Description

SKIL / Madali

Thread Size: 1-1/4", Nut Height: 3/8", Head Width: 1-5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN924105
Minimum Qty (MOQ):	1 EA
NSN:	5310-00-063-1608
Schedule B:	7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

ANIO2416C



^{*} See page 2 for technical characteristics

P/N AN924-16S Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.330 Inches Minimum And 0.422 Inches Maximum
Width Across Flats:	1.609 Inches Minimum And 1.641 Inches Maximum
Thread Series:	Un
Thread Quantity Per Inch:	12
Nominal Thread Size:	1.312 Inches
Bearing Surface Type:	Chamfered Or Washer Faced
Material:	Steel Comp 347 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall

How to Order

Order this fitting nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-16S and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-16S and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-16S and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/AN924-16S and selecting the quantity you want https://military-fasteners.com/nuts/AN924-16S and selecting the your cart you can be selected as a selecting the property of the property of the your cart you can be selected as a selecting the your cart you can be selected as a selecting the your cart you can be selected as a selecting the your cart you can be selected as a selecting