

P/N AN924-24J

Description

Thread Size: 1-7/8", Nut Height: 3/8", Head Width: 2-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

National Motor Freight:

| SKU / Model: | AN92424J |
|--------------------|------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5310-00-935-3725 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |

093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN924-24J Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Nut Style: | Hexagon |
| Nut Height: | 0.390 Inches Minimum And 0.422 Inches Maximum |
| Width Across Flats: | 2.168 Inches Minimum And 2.208 Inches Maximum |
| Thread Series: | Un |
| Thread Quantity Per Inch: | 12 |
| Nominal Thread Size: | 1.875 Inches |
| Countersink Angle: | 90.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Qq-s-763 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Overall |

How to Order

Order this fitting nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-24] and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-24] and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-24] and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-24] and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/AN924-24] and selecting the quantity you want the property of the propert