

## **P/N AN924-5K**

### **Description**

Thread Size: 1/2", Nut Height: 17/64", Head Width: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN9245K
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-456-6726
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN924-5K Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.234 Inches Minimum And 0.266 Inches Maximum
Width Across Flats:	0.746 Inches Minimum And 0.753 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Bearing Surface Type:	Chamfered
Material:	Steel Comp 316 Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall

## **How to Order**

Order this fitting nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-5K">https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-5K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-5K">https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-5K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-5K">https://military-fasteners.com/nuts/plain+hexagon+nuts/AN924-5K</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/AN924-5K">https://military-fasteners.com/nuts/AN924-5K</a> and selecting the quantity you want <a href="https://military-fasteners.com/nuts/AN924-5K">https://military-fasteners.com/nuts/AN924-5K</a> and selecting the property of the prope