

Description

Tube outer diameter: 5/8", flared tube, pressure seal, corrosion resistant steel, AN929 series cap

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN92910J |
| Minimum Qty (MOQ): | 1 |
| NSN: | 4730-00-835-1531 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



P/N AN929-10J Specifications

| | |
|--|--|
| Thread Class: | 3b Internal |
| Thread Direction: | Right-hand Internal |
| Tube Outside Diameter For Which Designed: | 0.625 Inches Nominal |
| Connection Style: | Pressure Seal Flared |
| Seat Angle: | 37.0 Degrees |
| Material: | Steel Comp 316 Cap Or Steel Comp 304 Cap |
| Material: | Steel Comp 316 Nut Or Steel Corrosion Resisting Nut |
| Material Document And Classification: | 66,aisi 316/sae 30316 Fed Std 1st Material Response Cap Or 66,siai 304/sae 30304 Fed Std 2nd Material Response Cap |
| Material Document And Classification: | 66,aisi316/sae 30316 Fed Std 1st Material Response Nut |
| Surface Treatment: | Passivate Overall |
| Style Designator: | Cap, Tube, Flared |
| Specification/standard Data: | 88044-an929 Government Standard And 81343-as4841 Professional/Industrial Association Standard |

How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/AN929-10J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.