

# P/N AN929-3

Military-Fasteners.com

#### Description

Outer diameter: 3/16", flared tube fitting, pressure seal aluminum, blue color, AN929 series fitting

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AN9293
Minimum Qty (MOQ):	10
NSN:	4730-00-221-2126
Schedule B:	7612.90.5000
ECCN:	EAR99
National Motor Freight:	051400, Pipe Fittings Aluminum



## P/N AN929-3 Specifications

Thread Class: 3	3b Internal
<b>Fhread Direction:</b>	Right-hand Internal
Fube Outside Diameter For Which C   Designed: C	0.188 Inches Nominal
End Item Identification:	Aircraft And Helicopter Applications
Connection Style: F	Pressure Seal Flared
Unable To Decode:	Unable To Decode
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size: 0	0.375 Inches Internal
Seat Angle: 3	37.0 Degrees
Material: A	Aluminum Alloy 7075 Overall Or Aluminum Alloy 2014 Overall
Material: A	Aluminum Alloy 7075 Or Aluminum Alloy 2014 Overall
Material Document And Classification:	Qq-a-268,t6 Fed Spec 1st Material Response Overall Or Qq-a-268,t851 Fed Spec 1st Material Response Overall Or Qq-a-266,t6 Fed Spec 2nd Material Response Overall
Material Document And Classification:	Qq-a-268,t6 Fed Spec 1st Material Response Or Qq-a-268,t851 Fed Spec 1st Material Response Or Qq-a-266,t6 Fed Spec 2nd Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Style Designator: 0	Cap, Tube, Flared
Thread Series Designator:	Unf Internal
Specification/standard Data:	88044-an929 Government Standard And 81343-as4841 Professional/industrial Association Standard

### How to Order

Order this tube cap from our inventory online by visiting <u>https://military-fasteners.com/fittings/tube+caps/AN929-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.