

Description

Outer diameter: 3/16", flared tube fitting, pressure seal, corrosion resistant steel, gray color, AN929 series cap

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN9293J
Minimum Qty (MOQ):	1
NSN:	4730-00-725-1975
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



P/N AN929-3J Specifications

Thread Class:	3b Internal
Thread Direction:	Right-hand Internal
Tube Outside Diameter For Which Designed:	0.188 Inches Nominal
End Item Identification:	Aircraft, Acml29, C135, F4, F15, H3, Hh60,sh60,ta4j,ov10
Connection Style:	Pressure Seal Flared
Unable To Decode:	Unable To Decode
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.375 Inches Internal
Seat Angle:	37.0 Degrees
Criticality Code Justification:	Feat
Special Features:	Weapon System Essential
Material:	Steel Comp 304 Cap
Material:	Steel Comp 304 Nut Or Steel Comp 316 Nut
Material:	Steel Comp 304 Or Steel Comp 316 Nut
Material Document And Classification:	Fed Std 66 Fed Std All Material Responses Nut
Material Document And Classification:	Fed Std 66 Fed Std Single Material Response Cap
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
Style Designator:	Cap, Tube, Flared
Thread Series Designator:	Unjf Internal
Specification/standard Data:	88044-an929 Government Standard And 81343-as4841 Professional/industrial Association Standard

How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/AN929-3J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.