

Description

Outer diameter: 5/16", flared tube fitting, pressure seal corrosion resistant steel, gray color, military standard MIL-F-5509, AN929 series cap

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN9295J](#)

| | |
|-------------------------|---|
| SKU / Model: | AN9295J |
| Minimum Qty (MOQ): | 2 |
| NSN: | 4730-00-541-1207 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 052190, Pipe,tubing,or Pipe Or Tubing Fitti |



P/N AN929-5J Specifications

| | |
|---|---|
| Thread Class: | 3b Internal |
| Thread Direction: | Right-hand Internal |
| Tube Outside Diameter For Which Designed: | 0.312 Inches Nominal |
| Connection Style: | Pressure Seal Flared |
| Nominal Thread Size: | 0.500 Inches Internal |
| Seat Angle: | 37.0 Degrees |
| Material: | Steel Comp 304 Overall |
| Material Document And Classification: | Qq-s-763 Fed Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Overall |
| Style Designator: | Cap, Tube, Flared |
| Thread Series Designator: | Unf Internal |
| Specification/standard Data: | 88044-an929 Government Standard And 81343-as4841 Professional/Industrial Association Standard |

How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/AN929-5J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.