

Description

Tube outer diameter: 1/2", flared tube fitting, pressure seal corrosion resistant steel, AN929 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN9298J
Minimum Qty (MOQ):	1
NSN:	4730-00-541-1206
Schedule B:	7318..
ECCN:	EAR99
National Motor Freight:	052190, Pipe,tubing,or Pipe Or Tubing Fitti



* See page 2 for technical characteristics

P/N AN929-8J Specifications

Thread Class:	3b Internal
Thread Direction:	Right-hand Internal
Tube Outside Diameter For Which Designed:	0.500 Inches Nominal
Connection Style:	Pressure Seal Flared
Unable To Decode:	Unable To Decode
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch
Nominal Thread Size:	0.750 Inches Internal
Seat Angle:	37.0 Degrees
Material:	Steel Comp 304 Cap
Material:	Steel Comp 304 Nut
Material Document And Classification:	Fed Std66 Fed Std All Material Responses Nut
Material Document And Classification:	Fed Std66 Fed Std Single Material Response Cap
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35,type 1 Fed Spec Single Treatment Response Overall
Style Designator:	Cap, Tube, Flareless
Thread Series Designator:	Unf Internal
Specification/standard Data:	88044-an929 Government Standard And 81343-as4841 Professional/Industrial Association Standard

How to Order

Order this tube cap from our inventory online by visiting <https://military-fasteners.com/fittings/tube+caps/AN929-8J> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.