

Description

size: 5/16, thickness: 1/32", corrosion resistant steel, passivated finish, AN960 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[AN960-C516L](#) [NAS1149C0532R](#)

SKU / Model:	AN960C516L
Minimum Qty (MOQ):	100
NSN:	5310-00-167-0814
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N AN960C516L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.318 Inches Minimum And 0.338 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.022 Inches Minimum And 0.042 Inches Maximum
Overall Diameter:	0.557 Inches Minimum And 0.582 Inches Maximum
Material:	Steel Corrosion Resisting Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Overall And Mil-s-6721 Mil Spec 2nd Material Response Overall And Mil-s-6721 Mil Spec 3rd Material Response Overall And Mil-s-6721 Mil Spec 4th Material Response Overall
Surface Treatment:	Passivate Overall
Nondefinitive Spec/std Data:	A Type And 2 Grade And B Class

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/AN960C516L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.