

P/N AN960C516L

Description

size: 5/16, thickness: 1/32", corrosion resistant steel, passivated finish, AN960 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

AN960-C516L NAS1149C0532R

SKU / Model: AN960C516L

Minimum Qty (MOQ): 100

NSN: 5310-00-167-0814

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









^{*} See page 2 for technical characteristics

P/N AN960C516L Specifications

| Cross-sectional Shape Style: | Rectangular |
|------------------------------|--|
| Hole Diameter: | 0.318 Inches Minimum And 0.338 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Center Hole Shape Style: | Round |
| Thickness: | 0.022 Inches Minimum And 0.042 Inches Maximum |
| Overall Diameter: | 0.557 Inches Minimum And 0.582 Inches Maximum |
| Material: | Steel Corrosion Resisting Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall |
| Material Document And | Mil-s-5059 Mil Spec 1st Material Response Overall And Mil-s-6721 Mil Spec 2nd Material Response Overall And Mil-s-6721 Mil Spec 3rd Material |
| Classification: | Response Overall And Mil-s-6721 Mil Spec 4th Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Nondefinitive Spec/std Data: | A Type And 2 Grade And B Class |

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/AN960C516L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.