

**Description**

size: 5/16, thickness: 1/32", corrosion resistant steel, passivated finish, AN960 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[AN960-C516L](#) [NAS1149C0532R](#)

SKU / Model:	AN960C516L
Minimum Qty (MOQ):	100
NSN:	5310-00-167-0814
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N AN960C516L Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.318 Inches Minimum And 0.338 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Center Hole Shape Style:</b>	Round
<b>Thickness:</b>	0.022 Inches Minimum And 0.042 Inches Maximum
<b>Overall Diameter:</b>	0.557 Inches Minimum And 0.582 Inches Maximum
<b>Material:</b>	Steel Corrosion Resisting Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
<b>Material Document And Classification:</b>	Mil-s-5059 Mil Spec 1st Material Response Overall And Mil-s-6721 Mil Spec 2nd Material Response Overall And Mil-s-6721 Mil Spec 3rd Material Response Overall And Mil-s-6721 Mil Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Nondefinitive Spec/std Data:</b>	A Type And 2 Grade And B Class

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/AN960C516L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.