

P/N AN960C716L

Description

size: 7/16, thickness: 1/32", corrosion resistant steel, passivated finish, AN960 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1149C0732R

SKU / Model: AN960C716L

Minimum Qty (MOQ): 100

NSN: 5310-00-275-0616


ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi









P/N AN960C716L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.443 Inches Minimum And 0.463 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.022 Inches Minimum And 0.042 Inches Maximum
Overall Diameter:	0.745 Inches Minimum And 0.770 Inches Maximum
Material:	Steel Corrosion Resisting Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
Material Document And	Mil-s-5059 Mil Spec 1st Material Response Overall And Mil-s-6721 Mil Spec 2nd Material Response Overall And Mil-s-6721 Mil Spec 3rd Material
Classification:	Response Overall And Mil-s-6721 Mil Spec 4th Material Response Overall
Nondefinitive Spec/std Data:	A Type And 2 Grade And B Class

How to Order

Order this flat washer from our inventory online by visiting https://military-fasteners.com/washers/flat+washers/AN960C716L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/AN960C716L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/AN960C716L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/flat+washers/AN960C716L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/AN960C716L and selecting the property of t