

**Description**

size: 1/2", thickness 1/32", corrosion resistant steel, passivated finish, AN960 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[NAS1149C0832R](#)

SKU / Model:	AN960C816L
Minimum Qty (MOQ):	100
NSN:	5310-00-306-3167
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

# P/N AN960C816L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.505 Inches Minimum And 0.525 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.022 Inches Minimum And 0.042 Inches Maximum
Overall Diameter:	0.870 Inches Minimum And 0.895 Inches Maximum
End Item Identification:	W/s:aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Missile, Air-to-air, Sparrow (aim-7); Missile, Air-to-air, Phoenix (aim-54); Missile, All-weather Anti-ship, Harpoon (agm-84); Radar Set, An/tpn-18; Engine, Aircraft Tf33-pw-102 (c-135e, Ec-135h/k/p); Systems, Jp-5 Aviation Fuels; Support Equipment, B-1 Aircraft; Engine, Aircraft Tf33-p-3/5/9 (c/ec-135,b-52h)
Material:	Steel Corrosion Resisting Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall
Material Document And Classification:	Mil-s-5059 Mil Spec 1st Material Response Overall And Mil-s-6721 Mil Spec 2nd Material Response Overall And Mil-s-6721 Mil Spec 3rd Material Response Overall And Mil-s-6721 Mil Spec 4th Material Response Overall
Surface Treatment:	Passivate Overall

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/AN960C816L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.