

Description

Hole Diameter: 1-1/4", Diameter: 1"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN960KD2016L |
| Minimum Qty (MOQ): | 55 EA |
| NSN: | 5310-01-319-5872 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991. |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N AN960KD2016L Specifications

| | |
|---|--|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 1.255 Inches Minimum And 1.275 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.013 Inches Minimum And 0.019 Inches Maximum |
| Overall Diameter: | 1.995 Inches Minimum And 2.020 Inches Maximum |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-250/5,cond T3 Or T4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541,class 1a Mil Spec 2nd Treatment Response Overall Or Mil-a-8625,ty 1 Or Ty 2 Mil Spec 1st Treatment Response Overall |
| Nondefinitive Spec/std Data: | A Type And 1 Grade And D Class |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/AN960KD2016L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.