

**Description**

Hole Diameter: 9/16", Diameter: 1-5/64", Thickness: 1/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN960KD916L
Minimum Qty (MOQ):	100 EA
NSN:	5310-01-162-5736
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE  
AVAILABLE

## P/N AN960KD916L Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.578 Inches Nominal
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.016 Inches Nominal
<b>Overall Diameter:</b>	1.057 Inches Minimum And 1.082 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Qq-a-250/5,temper T3 Fed Spec Single Material Response Overall Or Qq-a-250/5,temper T4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Nondefinitive Spec/std Data:</b>	A Type And 1 Grade And D Class

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/AN960KD916L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.