

P/N AN961-416T

Military-Fasteners.com

Description

Hole Diameter: 1/4", Diameter: 1/2", Thickness: 1/16",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN961416T
Minimum Qty (MOQ):	100
NSN:	5310-00-177-1156
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



P/N AN961-416T Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.225 Inches Minimum And 0.275 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.054 Inches Minimum And 0.074 Inches Maximum
Overall Diameter:	0.495 Inches Minimum And 0.520 Inches Maximum
End Item Identification:	W/s: Engine, Aircraft, F110-ge-100/129 (f-16c/d); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Guided Missile Launching System, Mk 26 (gmls); Support Equipment, B-1 Aircraft; Aircraft, C-2a (reprocured); Trainer, B-1b Aircraft; Close In Weapon System (ciws-phalanx); Tactical Air Opns Module (an/tyq-(23)); Deep Submergence Systems Programs (dssp)
Material:	Copper Alloy 270 Overall Or Copper Alloy 268 Overall
Material Document And Classification:	Qq-w-321 1/2 Hard Fed Spec 1st Material Response Overall Or Qq-b-626 1/2 Hard Fed Spec 2nd Material Response Overall
Surface Treatment:	Tin Overall
Surface Treatment Document And Classification:	Mil-t-10727 Ty 1 Mil Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <u>https://military-fasteners.com/washers/flat+washers/AN961-416T</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.