

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AS125141 |
| Minimum Qty (MOQ): | 60 EA |
| NSN: | 5320-00-840-1663 |
| Schedule B: | 7318.23.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AS125141 Specifications

| | |
|--|--|
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.125 Inches Nominal |
| Shank Style: | Straight |
| Head Major Diameter: | 0.216 Inches Nominal |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Overall |
| Material Document And Classification: | Ams 7225 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AS125141> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.