

## Description


Fastener Length: 1/4",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AS125272
Minimum Qty (MOQ):	100
NSN:	5320-00-117-6939
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



# P/N AS125272 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.175 Inches Minimum And 0.183 Inches Maximum
End Item Identification:	W/s:teammate, An/trq-32; Radar Set, An/tpn-18; Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Communications Terminal, Satellite An/gsc-39(v)1; Traffic Jam, An/tlq-17a; Aircraft, Thunderbolt II, A-10; Support Equipment, B-52 Aircraft; Support Equipment, B-1 Aircraft; Missile, Advanced Medium Range Air-to-air (amraam)/aim120a
Countersink Angle:	99.5 Degrees Minimum And 100.5 Degrees Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AS125272> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.