

Description

thread: 1/4-28 taper, straight fitting, lubrication hydraulic surface check, steel, AS15001 series fitting

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1680-AS](#)

SKU / Model:

AS150012P

Minimum Qty (MOQ):

10

NSN:

4730-01-602-6883

ECCN:

EAR99



* See page 2 for technical characteristics

P/N AS15001-2P Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Screw Thread Series Designator: | Uns |
| Width Across Flats: | 0.309 Inches Minimum And 0.315 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.25 Inches |
| Part Name Assigned By Controlling Agency: | Fitting,lubrication,hydraulic |
| Height: | 0.875 Inches Minimum And 0.999 Inches Maximum |
| Material: | Steel Body |
| Material Document And Classification: | Boeing Supplement To As15001, Carbon Steel Mfr Ref Single Material Response Body |
| Style Designator: | Straight |

How to Order

Order this lubrication fitting from our inventory online by visiting <https://military-fasteners.com/fittings/lubrication+fittings/AS15001-2P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.