

Description

Thread Size: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AS21909
Minimum Qty (MOQ):	5 EA
NSN:	4730-00-134-8256
National Motor Freight:	052250, Pipe R Tubing R Pipe Fittings Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AS21909 Specifications

Thread Class:	3a 3rd End Bulkhead
Thread Class:	3a All Ends
Maximum Operating Temp:	135.0 Deg Celsius Single Response
End Item Identification:	S-3a Viking Aircraft
Connection Style:	Flareless (tube) All Ends
Leg Length:	1.312 Inches Nominal 1st End
Leg Length:	1.312 Inches Nominal 2nd End
Leg Length:	1.969 Inches Nominal 3rd End
Connection Type:	Threaded External Tube All Ends
Maximum Operating Pressure:	3000.0 Pounds Per Square Inch Single Response
Nominal Thread Size:	0.750 Inches 3rd End Bulkhead
Nominal Thread Size:	0.750 Inches All Ends
Seat Angle:	12.0 Degrees All Ends
Nominal Outside Diameter Tube Accommodated:	0.500 Inches 3rd End Bulkhead
Nominal Outside Diameter Tube Accommodated:	0.500 Inches All Ends
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-367,t73 Fed Spec Single Material Response Overall
Media For Which Designed:	Fluid Single Response
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,tydpe2,class 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf 3rd End Bulkhead
Thread Series Designator:	Unjf All Ends
Specification/standard Data:	96906-ms21909 Government Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AS21909> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.