

P/N AS21919WCG19

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | AS21919WCG19 |
|-------------------------|-----------------------------|
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5340-00-955-2995 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



^{*} See page 2 for technical characteristics

P/N AS21919WCG19 Specifications

| Tongue Hole Type: | Round, Unthreaded |
|---|--|
| Cushioning Environmental Protection: | Weather Resistant |
| Overall Width: | 0.500 Inches Nominal |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.032 Inches Nominal |
| Center To Center Distance Between Loop And Mounting Hole: | 1.061 Inches Nominal |
| Distance From Loop Center To Tongue End: | 1.279 Inches Nominal |
| Loop Inside Diameter: | 1.188 Inches Nominal |
| Special Features: | Cushion Ozone Resistant |
| Material: | Rubber Chloroprene Class Cr Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | Ams 3209 Assn Std Single Material Response Cushion |
| Material Document And Classification: | Ams 5510 Assn Std Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |

How to Order

Order this clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/AS21919WCG19 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.