

P/N AS21919WCH06

Description

Diameter: 13/64", steel corrosion resisting band

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AS21919WCH06

Minimum Qty (MOQ): 10

NSN: 5340-01-528-0384

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









^{*} See page 2 for technical characteristics

P/N AS21919WCH06 Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.500 Inches Nominal
Diameter:	0.208 Inches Minimum And 0.218 Inches Maximum
Material Thickness:	0.032 Inches Nominal
End Item Identification:	Fuel/elec
Material Diameter:	0.062 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.592 Inches Nominal
Distance From Loop Center To Tongue End:	0.811 Inches Nominal
Loop Inside Diameter:	0.375 Inches Nominal
Material:	Silicon Cushion
Material:	Steel Corrosion Resisting Band
Material Document And Classification:	Ams 3310 Assn Std Single Material Response Cushion
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/AS21919WCH06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WCH06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WCH06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WCH06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/asa1919WCH06 and selecting the fasteners.