

P/N AS21919WCJ14

Description

Diameter: 13/64", steel corrosion resisting band

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

MS21919WCJ14

SKU / Model: AS21919WCJ14

Minimum Qty (MOQ): 5

NSN: 5340-01-526-4605

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi









^{*} See page 2 for technical characteristics

P/N AS21919WCJ14 Specifications

Tongue Hole Type:	Round, Unthreaded
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
Center To Center Distance Between Loop And Mounting Hole:	0.827 Inches Minimum And 0.857 Inches Maximum
Distance From Loop Center To Tongue End:	1.050 Inches Minimum And 1.070 Inches Maximum
Loop Inside Diameter:	0.735 Inches Minimum And 0.765 Inches Maximum
Special Features:	Maximum Recommended Temperature Range Is 450 Deg Fahrenheit
Material:	Rubber Fluorosilicone Class Fq Cushion
Material:	Steel Corrosion Resisting Band
Surface Treatment:	Passivate Band
Style Designator:	Single Loop

How to Order

Order this loop clamp from our inventory online by visiting https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/clamps/asa1919WCJ14 and selecting the property of the property of