

Description


Diameter: 13/64", steel comp band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AS21919WCJ16
Minimum Qty (MOQ):	5
NSN:	5340-01-156-5483
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N AS21919WCJ16 Specifications

Tongue Hole Type:	Round, Unthreaded
Cushioning Environmental Protection:	Oil Resistant And Fuel Resistant
Overall Width:	0.490 Inches Minimum And 0.510 Inches Maximum
Diameter:	0.199 Inches Minimum And 0.209 Inches Maximum
Material Thickness:	0.032 Inches Nominal
End Item Identification:	Mrap Rg-33
Center To Center Distance Between Loop And Mounting Hole:	0.936 Inches Minimum And 0.966 Inches Maximum
Distance From Loop Center To Tongue End:	1.169 Inches Nominal
Loop Inside Diameter:	0.985 Inches Minimum And 1.015 Inches Maximum
Material:	Rubber Fluorosilicone Class Fq Cushion
Material:	Steel Comp 321 Band
Material Document And Classification:	Mil-r-25988 Type 2 Class 1 Grade 60 Mil Spec Single Material Response Cushion
Material Document And Classification:	Mil-s-6721 Mil Spec Single Material Response Band
Surface Treatment:	Passivate Band
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Band
Style Designator:	Offset Mount

How to Order

Order this loop clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/AS21919WCJ16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.